

## SAVANA CLICK SPC MAINTENANCE GUIDE

### Introduction

Thank you for your purchase of flooring by LG Hausys America, Inc. An effective maintenance program will protect your new resilient flooring and will provide years of performance. Maintenance should be performed according to foot traffic, temperature, etc. Although general maintenance programs should be performed, customized programs set to your unique conditions should be followed to maximize the results and the overall life of the floor.

### During and Immediately after Installation

Remove dirt and other foreign materials that can cause trip hazards and can damage the flooring by foot traffic.

#### 1. Initial Maintenance

- ✓ Remove dirt and other foreign materials thoroughly with a microfiber dust mop or broom. 
- ✓ Use an appropriate pH neutral cleaning solution and dilute according to the manufacturer's dilution ratio recommendations.
- ✓ Damp mop the floor, being careful not to flood the floor with excess water.
- ✓ Stubborn areas should be allowed to soak for 5~10 minutes then have the excess moisture mopped off of the floor.
- ✓ For larger areas, use a scrubber dryer or rotary machine (150-300 rpm) with a 3M blue or red pad or equivalent. Do not use a black or brown pad. Pick up dirty water, rinse with clean water and allow to dry.  
- ✓ Soak leftover residues.
- ✓ Damp mop only with a micro-fiber pad. Dry floor completely after cleaning heavily soiled areas.
- ✓ For small areas use a damp micro-fiber pad/mop in place of the machine, dilute cleaning solution as recommended, rinse well, and allow to dry. 

#### 2. Regular Maintenance

- ✓ Sweep often to prevent dirt build up or scratches.
- ✓ Mix cleaning solution and water according to dilution ratio as recommended by the manufacturer.
- ✓ Damp mop the floor with a micro fiber pad.

Additional cleaning may be necessary for hard to clean or stubborn areas. Always clean and rinse with clean water.

### Sweeping and Mopping

Vacuum cleaners with beater bars are not recommended for removing loose debris from the



**LG Hausys America, Inc.**

900 Circle 75 Parkway Suite 1500 Atlanta, GA 30339

[www.lghausysusa.com](http://www.lghausysusa.com)

flooring surface. Hard objects can get trapped in the beater bar and damage the flooring material. Mico-fiber dust mops and damp mops are recommended for general cleaning.

### **Use of Floor Care Chemicals**

The improper use of cleaning chemicals may cause damage and/ or discoloration. Overuse or inadequate rinsing of cleaning chemicals may compromise the performance of the floor.

Abrasive powders or cleansers should not be used. Do NOT use highly alkaline products (ammonia, soda) or strong solvents such as acetone as they can be harmful to both people and to your floor.

### **Do I need to polish my floor?**

The out of the box factory finish was designed to be both appealing and durable. The advanced surface finish, StoneShield Coating, applied to PrestG does not require the use of polish. Wax based polishes are not approved for use on PrestG flooring as it will not adhere to the surface finish and will cause an unappealing appearance.

### **How often should I clean my floor?**

The best cleaning schedule for your new flooring should be determined by how much and what type of traffic it gets. To determine how often to clean the floors, answer the following questions:

- ✓ Is the flooring dark or light colored?
- ✓ Are there exterior entrances near the flooring?
- ✓ What level of traffic will the flooring be subjected to?
- ✓ What type of debris will the foot traffic introduce to the flooring?